

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

<http://www.baumer.nt-rt.ru> || brf@nt-rt.ru

СИСТЕМЫ ПОЗИЦИРОВАНИЯ

Технические характеристики

Format adjustment

Sample picture	Product family	Dimensions	Shaft type	Features
	BG440 - planetary gearing	ø52 x 155.5 mm (BG440.25) ø52 x 180.5 mm (BG440.50)	ø12 mm solid shaft	• EC-motor with planetary gearing• for automated spindle positioning cycles
	BG650 - planetary gearing	ø52 x 176.5 mm (BG650.25) ø52 x 201.5 mm (BG650.50) ø52 x 226.5 mm (BG650.75)	ø12 mm solid shaft	• EC-motor with planetary gearing• for automated spindle positioning cycles
	GK473	22.6 x 99 x 114.5 mm	-	• Fieldbus interface for spindle position displays• CANopen®, DeviceNet, Profibus-DP
	MSBA 42	ø42 mm	ø8 mm solid shaft	• DC motor, brush-type• Absolute multiturn position detection, CANopen®
	MSIA 42 CANopen	42 x 95 mm	ø6 mm solid shaft ø8 mm solid shaft	• DC motor, brushless• Absolute multiturn position detection, CANopen®
	MSIA 42 Profibus	42 x 95 mm	ø6 mm solid shaft ø8 mm solid shaft	• DC motor, brushless• Absolute multiturn position detection, Profibus-DP
	MSIA 68 bevel gear transmission V6 CANopen	ø68 mm	ø12 mm (through hollow shaft)	• DC motor, brushless• Absolute multiturn position detection, CANopen®
	MSIA 68 bevel gear transmission V6 Profibus	ø68 mm	ø12 mm (through hollow shaft)	• DC motor, brushless• Absolute multiturn position detection, Profibus-DP
	MSIA 68 bevel gear transmission W3 CANopen	ø68 mm	ø12 mm (through hollow shaft)	• DC motor, brushless• Absolute multiturn position detection, CANopen®
	MSIA 68 bevel gear transmission W3 Profibus	ø68 mm	ø12 mm (through hollow shaft)	• DC motor, brushless• Absolute multiturn position detection, Profibus-DP
	MSIA 68 planetary gear transmission CANopen	ø68 mm	ø10 mm solid shaft ø14 mm solid shaft	• DC motor, brushless• Absolute multiturn position detection, CANopen®

				
	MSIA 68 planetary gear transmission Profibus	ø68 mm	ø10 mm solid shaft ø14 mm solid shaft	• DC motor, brushless • Absolute multiturn position detection, Profibus-DP
	MSIA 68 spur gear transmission CANopen	ø69 mm	ø10 mm solid shaft	• DC motor, brushless • Absolute multiturn position detection, CANopen®
	MSIA 68 spur gear transmission Profibus	ø69 mm	ø10 mm solid shaft	• DC motor, brushless • Absolute multiturn position detection, Profibus-DP
	N 150	37 x 75 x 45 mm	ø14 mm (through hollow shaft)	• Through hollow shaft max. ø14 mm, manual format alignment • Display LCD two lines, interface RS485
	N 152	37 x 75 x 45 mm	ø14 mm (through hollow shaft)	• Through hollow shaft max. ø14 mm, automated format alignment • Display LCD two lines, interface RS485
	N 155	37 x 75 x 29 mm	-	• Plug-on mount, enter key, manual format alignment • Display LCD two lines, interface RS485
	N 242	144 x 144 x 116.5 mm	-	• Manual and automated format alignment • Display LCD two lines, interface RS485

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93